

National Center for Biological Sciences

Tata Institute of Fundamental Research

GKVK, Bellary Road, Bangalore 560 065. India

Tel. No: 080 2366, 6346 Email: vinuthaks@ncbs.res.in, www.ncbs.res.in

Ref:NCB/CM19-465/190610

July 04, 2019

ENQUIRY

To

=> By Speed Post/Courier

Dear Sirs

Please let us have your Quotation for the following:

S.No.	Item Description	Qty	UOM
1	Supply of Pre Filters, Micro Filters, Bag Type Filters, HEPA Filters for AHU's.	1.00	LOT
14	As per the Sizes and the Detailed specification, attached.		

The bids are liable to be rejected if the sealed envelope is not addressed to "THE HEAD-PURCHASE? with Tender Ref No. and Item Description and due date. The bids delivered in person shall be dropped in Purchase Section. If the bids are sent through courier or mail, it should reach by submission date and time and NCBS will not be responsible for the delay.

2. DUE DATE FOR SUBMISSION OF QUOTATION AGAINST THIS ENQUIRY IS 25/07/2019 BY 5.30PM.

- 3.QUOTATIONS RECEIVED AFTER THE DUE DATE SHALL BE REJECTED.
- 4. The validity of your quotation should be for 60 days from the due date.
- 5.All duties, taxes, surcharge and cess as currently applicable must be stated in yourquotation, separately. Otherwise your quote is liable to be rejected.
- 6. Your quotation should indicate delivery period & warranty period.
- 7.Delivery to be made to our stores. Please indicate charges, if any extra. Transit Insurance should be done upto NCBS Stores.
- 8.If you are unable to supply the quality, specifications or brand as mentioned in our enquiry, please state so and then offer alternative to quality/specifications.
- 9.Payment: within one month after delivery & acceptance/satisfactory installation.
- 10.Please ensure that the enquiry number and the due date is superscribed on the envelope failing which your quotation is liable to be rejected.
- 11.Since we are a public funded research institution, we are exempted from paying Customs duty (Except advolerum duty of 5% + 2%Cess and 1% Cus Sec & High Edu. CESS vide Notification No.51/96 with latest amendments) and excise duty vide Notification No. 10/97 CENTRAL EXCISE dated 01-03-1997 for all scientific equipments, technical instruments, equipments (including computers), their accessories, spares, consumables and software. Hence, please offer your prices
- 12.If the item is covered under DGS&D rate contract, please quote the rate as per the DGS&D rate contract with xerox copy of the DGS&D order.

13. Any dispute or differences that may arise between the parties shall be referred to the sole arbitration of the Centre Director or his nominees. The decision of the arbitrator shall be final and binding on the parties. The venue for arbitration shall be Bangalore. The provisions of the Arbitration and Conciliation Act, 1996 as amended from time to time shall apply. The courts in Bangalore shall have exclusive jurisdiction to deal with any or all disputes between the parties.

14.TIFR is a public funded research institute and is entitled to concessionalrate of GST @ 5%for certain items supplied for reresearch purpose vide notification no. 47/2017 and 45/2017 dated 14th Nov, 2017. The offer should be submitted after fully considering the above notification.

15.Liquidity Damages:If the equipment/ items as per specifications in our P.O. is not supplied (shipped) within the specified delivery schedule, then liquidated damages (not in terms of penalty) will be imposed automatically and shall be deducted from the bill at the rate of 0.5% per week subject to a maximum of 10% of the order value.

16.Income Tax at the applicable rates as per the Indian Income Tax Act 1961 will be deducted at source for the services availed / ordered. In case of service provider, the rate of tax deduction shall be at 2% as per Section 194C, and in case of fee for professional / technical services under section 194J, the tax reduction shall be at the rate of 10%. In case service provider does not provide PAN number, the deduction shall be at 20% under section 206 AA.

-Tax Deduction Certificates will be provided on request for non PAN holders & Foreign Vendors and PAN holders could avail them through NSDL site dealing with 26AS.

SL No	Description	Qty no	y in os
1	PRE-FILTERS		
а	Box type Synthetic fibre filter, constructed out of non-woven synthetic fibre media we mesh on both sides & secured with anodized ductile aluminium mesh on both sides All the layers to be dully stiched together & to be housed in 18SWG Aluminium are sides to be sealed with Epoxy. With Neoperen gasket on the air out-let side. The have 11 Pleats/Rft, the pleats should be in a vertical manner. The filter shall have are down to 10 microns when tested as per BS: 2831 standard. The Filter should be bo & Air cleanable. It should be suitable for operation under 100% Relative Humidity temperature conditions. The velocity over the face of filter shall not exceed 105 MPM drop across the filter shall not exceed 3 mm WG for 50mm thick filter. The filter shandling units	s As detailed below, nodized frame and filter element shall an efficiency of 90% oth water washable by & 120 degree C	
	Pls Note the Filter media is required to be layered as below:		
	1st Layer - Anodized ductile aluminium mesh		
	2nd Layer - 40 sieve HDPE mesh		
	3rd Layer - Synthetic fibre media		
	4th Layer - 40 sieve HDPE mesh		
	5th Layer - Anodized ductile aluminium mesh		
	Size of the filters as mentioned below (H x W x D)mm		
	1 590 x 590 x 50		20
	2 490 x 595 x 20		20
	3 490 x 490 x 50		12 .
	490 x 290 x 50		10
	5 430 x 430 x 50	1	10
	6 430 x 290 x 50		10
	7 430 x 505 x 45		18
	845 x 590 x 48		6
	9 1075 x 380 x 48		6
	10 398 x 498 x 45		10
	398 x 498 x 48		10
	12 498 x 498 x 45		4
	398 x 498 x 45		3
	14 498 x 398 x 45		3
	15 610 x 610 x 50		20
	16 610 x 305 x 50		20
	17 500 x 700 x 46		30
	18 450 x 500 x 45		30
	19 500 x 610 x 25	3	30
b	Flange type All the Specifictaions same as the above Box Type Pre-filter		
	Size of the filters as mentioned below (H x W x D)mm		20
	1 250 x 750 x 100		30
Automotive Control	2 500 x 750 x 100		30
	3		25
	4 287 x 430 x 50		6 15
, in	5 610 x 610 x 50		5
	6 610 x 305 x 50		
	7 450 x 450 x 50		10

MICRO(FINE)-FILTERS Box Type Fine filters shall be designed to remove particles down to 5microns as per BS: 6540 standard. Filter shall comprise of aluminium sheet duly anodized. Filter element shall be made out of non-woven synthetic supported by anodized ductile aluminium mesh on both side & HDPE mesh not less than 40 sieve size on the both sides side with 11 Pleats/Rft of filtration area. All the layers to be dully stitched together. All sides to be sealed with ductile epoxy resin and filters shall be cleanable type using water/detergent. Rubber gaskets to be provided on the flange. Filter element shall be specially treated with antifungal and bacterial reagent to prevent growth of micro-organisms shall be screwed into the frame by means of an aluminium clamp patti and brass screws. They shall comprise of housing made from MS angles/flats epoxy coated of size suitable to receive the required number of filters to handle specified Cfm for each AHU. All filters shall be installed in same plane. No zigzagging shall be allowed by means of threaded bolts. PIS Note the Filter media is required to be layered as below: 1st Layer - Anodized ductile aluminium mesh 2nd Layer - 40 sieve HDPE mesh 3rd Layer - Synthetic fibre media 4th Layer - Anodized ductile aluminium mesh Size of the filters as mentioned below (H x W x D)mm 430 x 430 x 305 610 x 610 x 50 610 x 50 x 50 610 x 610 x 50 610 x 610 x 305 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 15 22 22
synthetic supported by anodized ductile aluminium mesh on both side & HDPE mesh not less than 40 sieve size on the both sides side with 11 Pleats/Rft of filtration area. All the layers to be dully stitched together. All sides to be sealed with ductile epoxy resin and filters shall be cleanable type using water/detergent. Rubber gaskets to be provided on the flange. Filter element shall be specially treated with antifungal and bacterial reagent to prevent growth of micro-organisms shall be screwed into the frame by means of an aluminium clamp patti and brass screws. They shall comprise of housing made from MS angles/flats epoxy coated of size suitable to receive the required number of filters to handle specified Cfm for each AHU. All filters shall be installed in same plane. No zigzagging shall be allowed by means of threaded bolts. PIs Note the Filter media is required to be layered as below: 1st Layer - Anodized ductile aluminium mesh 2nd Layer - 40 sieve HDPE mesh 3rd Layer - Synthetic fibre media 4th Layer - 40 sieve HDPE mesh 5th Layer - Anodized ductile aluminium mesh Size of the filters as mentioned below (H x W x D)mm 430 x 430 x 305 490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 22 22
Pls Note the Filter media is required to be layered as below: 1st Layer - Anodized ductile aluminium mesh 2nd Layer - 40 sieve HDPE mesh 3rd Layer - Synthetic fibre media 4th Layer - 40 sieve HDPE mesh 5th Layer - Anodized ductile aluminium mesh Size of the filters as mentioned below (H x W x D)mm 430 x 430 x 305 490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 22 22
1st Layer - Anodized ductile aluminium mesh 2nd Layer - 40 sieve HDPE mesh 3rd Layer - Synthetic fibre media 4th Layer - 40 sieve HDPE mesh 5th Layer - Anodized ductile aluminium mesh Size of the filters as mentioned below (H x W x D)mm 430 x 430 x 305 490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 22 22
2nd Layer - 40 sieve HDPE mesh 3rd Layer - 40 sieve HDPE mesh 5th Layer - Anodized ductile aluminium mesh Size of the filters as mentioned below (H x W x D)mm 430 x 430 x 305 490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 22 22
3rd Layer - Synthetic fibre media 4th Layer - 40 sieve HDPE mesh 5th Layer - Anodized ductile aluminium mesh Size of the filters as mentioned below (H x W x D)mm 430 x 430 x 305 490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 27 27
4th Layer - 40 sieve HDPE mesh 5th Layer - Anodized ductile aluminium mesh Size of the filters as mentioned below (H x W x D)mm 430 x 430 x 305 490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 27 27
Size of the filters as mentioned below (H x W x D)mm 430 x 430 x 305 490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 27 27
Size of the filters as mentioned below (H x W x D)mm 430 x 430 x 305 490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 27 27
430 x 430 x 305 490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 27 27
430 x 430 x 305 490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	15 27 27
490 x 490 x 305 610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	1! 2: 2:
610 x 610 x 50 610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	2:
610 x 305 x 50 FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	23
FLANGE TYPE MICROVEE FILTERS 610 x 610 x 300 611 x 305 x 300	
610 x 610 x 300 611 x 305 x 300	1.5
610 x 610 x 300 611 x 305 x 300	1:
611 x 305 x 300	1.
	5
450 x 450 x 150	10
430 X 430 X 130	
HEPA-FILTERS BOX TYPE	
HEPA FILTER, Box Type :Hepa filter will have Di Octyl Phthalate(DOP) test efficiency of 99.97% down to particle size of 0.3microns as per EN1822 with grades between H10 to H12,corresponding to MERV 17 as per IEST Type A.Hepa filter to be made of submicron glass fibre, tto be designed for a face velocity of 1.25m/s.(WXHXD)mm Size of the filters as mentioned below (H x W x D)mm	
450 450 150	
	12
	12
	4
010 X 202 X 200	4
Elange type All the Specifications same as the above Boy Type HEDA filter	
OLEC OF THE INTERS AS INCIDION OF A VA DJIMIN	
610 x 610 x 300	16
	5
NET STOCKET, STOCK DESCRIPTION AND THE TABLE OF	10
755 77 755 77 755	
Bag Filter	
Bag type filter will be with synthetic or glass fiber or FPCP media ,class F6 to F8,equivalent to MERV 10 to MERV 13 of ASHRAE 52.2 1999 with efficiency in (Range 2) between 50-65% and at least 85% in (Range 3).The filters will be so constructed to avoid leakage or bypass of air with suitable neoprene rubber gasket as required.	
Size of the filters as mentioned below (H x W x D)mm	
690 x 590 x 150 / 25	1:
	12
	12
430 x 430 x 300 / 20	6
430 × 290 × 300 / 20National Contract Contract	6
1	HEPA-FILTERS BOX TYPE HEPA FILTER, Box Type :Hepa filter will have Di Octyl Phthalate(DOP) test efficiency of 99.97% down to particle size of 0.3microns as per EN1822 with grades between H10 to H12,corresponding to MERV 17 as per IEST Type A.Hepa filter to be made of submicron glass fibre, tto be designed for a face velocity of 1.25m/s.(WXHXD)mm Size of the filters as mentioned below (H x W x D)mm 450 x 450 x 150 300 x 300 x 150 610 x 610 x 300 610 x 305 x 300 Flange type All the Specifictaions same as the above Box Type HEPA-filter Size of the filters as mentioned below (H x W x D)mm 610 x 610 x 300 610 x 305 x 300 450 x 450 x 300 Bag Filter Bag type filter will be with synthetic or glass fiber or FPCP media ,class F6 to F8,equivalent to MERV 10 to MERV 13 of ASHRAE 52.2 1999 with efficiency in (Range 2) between 50-65% and at least 85% in (Range 3).The filters will be so constructed to avoid leakage or bypass of air with suitable neoprene rubber gasket as required.

